KP-7500 Bump Bar

Spec Sheet

Document Details

Version Release Date: August 2026

Overview

This document provides the manufacturer’s specifications and technical details for the KP-7500 Bump Bar.

Download the latest version of this document here:

https://links.crunchtime.com/SS-KP7500BumpBar

… or scan the QR code to the left.



Feature	Specification		
Input	10 x 2, 20-Key Membrane		
Key Rating	30 Million Pushes		
Mounting Options	Optional Bracketing Available		
Overlay Options	Customizable Keypad Overlays, Installs without Tools		
Features	Software Programmable Scan Codes Adjustable Sound for Frequency and Volume Downloadable Firmware for Easy Updates and Support ControlPoint Supported		
Chassis	Durable, Premium Grade Polycarbonate Metal Reinforced Top for Extended Life Resistant to Extreme Temperatures, Water and Grease		
Dimensions	1.25” x 8.25” x 2.75” (H x W x D)		
Weight	10.4 ounces		
Power	Provided by Controller		
Audio	On-board Annunciator		
Interface Options		PS/2	USB
	Connection	6-pin Mini DIN	Mini-B USB
	Maximum Distance	50 feet	15 feet
Environmental	Operating Temperature	0° – 60° Celsius	
	Storage Temperature	-20° – 95° Celsius	
	Humidity	10% - 95%, non-condensing	
	Altitude	15,000 feet	
Certifications	FCC Part 15, Class A, EN55024, WEEE, CE, EU RoHS, China RoHS, MIC		
Warranty	Limited 3-Year Hardware Warranty		

© 2026 Crunchtime - All Rights Reserved | www.crunchtime.com |